

10/587629

Description

1

AP20 Rec'd PCT/PTO 28 JUL 2006

Distribution of short messages using a video control device

- 5 1. What technical features, or problems that can be solved
by technical features, form the basis of the invention?

In an IP-based network with video-centric services, i.e.
services with which a main part of the information is
10 transmitted as a video data stream (e.g. the "video on demand"
service) it should be possible to send an individual user
(Tln) a short message, e.g. a short message without
images/sounds by means of the short message service (SMS) or
to send a short message with images/sounds using the
15 multimedia message service (MMS) or the user should be allowed
to send a short message. In accordance with the invention,
this functionality is made available with the aid of the
control server for the video services and integrated into the
video image displayed on the TV set.

20

2. How has this problem been solved up to now?

Present video networks are mainly cable based. IP-based video
networks are relatively new and are at present being
25 implemented worldwide. Solutions that enable a user to
individually send or receive short messages are as yet unknown
for either IP- or cable-based networks.

Previous applications to integrate SMS messages in video
transmission have been limited to limiting the ability of the
30 particular user to send an SMS to a special number by means of
a mobile radio device and for the content of the SMS to be
then broadcast to all users, superimposed on the radiated TV
image as overlaid text.

3. How is the problem stated under item 1 solved by the invention?

Figure 1 shows an example of the invention, that is explained
5 in more detail in the following.

In an IP-based network with video-centric services a central video control device, e.g. a video control server, typically controls the video services. This video control server manages
10 the individual video users and their service profiles, controls the billing and controls the graphical user interface (GUI) displayed by means of the TV set connected to the set top box (STB). To control or select the services, a communication link, e.g. HTTP based, is provided between the client on the
15 STB and the video control server.

The method in accordance with the invention provides for the video control server to also support, as a new type of service, the reception and/or transmission of short messages
20 by a suitable application, e.g. an SMS/MMS application. For this purpose, the video Tln should be addressed by means of a standard PSTN call number. To do this, the video Tln subscribes to the video control server by means of its PSTN call number. Optionally, the addressing of the video Tln can
25 also be purely IP based, e.g. by means of a URI (e.g. teilnehmer@domain.de). In this case, the SMS/MMS distribution center will also have to have supported the transmission of SMS/MMS to such IP-based addresses.

30 Present day SMS/MMS distribution centers also support the transmission of SMS to PSTN Tln. The PSTN Tln in this case is addressed by means of its normal PSTN call number. At present this requires either special terminals (SMS in that case is transmitted, inband coded, using special protocols) or the SMS
35 is converted into language in the distribution center and read

to the PSTN Tln. MMS to PSTN Tln also requires a special terminal, moreover the distribution center for example sets up a voice channel and then sends the MMS to this via a modem link.

5

The method in accordance with the invention furthermore provides that the video control server logs on to the SMS/MMS distribution center in the name of all the video Tln managed by it. The PSTN call number of the video Tln is thus made
10 known to the distribution center. A new feature is that the entry in the distribution center takes place in such a way that the PSTN Tln can be reached via the video control server, i.e. the video control server acts as the "gateway" through which an SMS/MMS can be provided to the PSTN Tln (the video
15 control server terminates the SMS/MMS protocol of the public network and converts it to a format suitable for forwarding the SMS/MMS content to the application on the STB). The transmission of the SMS and MMS between the distribution center and video control server takes place through a suitable
20 interface, e.g. IP based.

The video control server contains an application for receiving and/or transmitting the SMS/MMS in accordance with SMS/MMS standards, i.e. the video control server contains the SMS/MMS
25 application for all the video Tln managed by it. Because the video control server terminates the SMS/MMS signaling in this application, an SMS/MMS transmitted to the video control server is also considered as successfully delivered.

30 The transmission of the actual content of the SMS/MMS to the video Tln takes place via an IP-based interface between the video control server and the STB, e.g. XML coded. According to the invention, the STB contains an application for this that can exchange actual data content of the SMS/MMS with the
35 particular SMS/MMS application on the video control server.

If the STB is online, i.e. has an IP connection, the application logs on to the STB for the SMS/MMS application on the video control server. As long as the STB is online, the SMS/MMS can receive the STB. The STB application changes the received data into a form that can be displayed as an image on the TV set connected to the STB. For an SMS, the characters contained are shown as text. For an MMS, the images contained and the characters are shown as an image with text. This image can then also be overlaid by an existing video image by the STB (note: present STB including present SW clients for video services support the required "alpha blending" technology for overlaying video images). If the STB is online but the TV set is switched off, several options are possible, as follows.

- The STB stores the SMS/MMS content temporarily and when the TV set is switched on displays a notice of received SMS/MMS in the form of a video image.
- The STB temporarily stores the SMS/MMS content and outputs an indication of received SMS/MMS to the STB (light on, sound via speaker).
- The STB automatically switches on a TV set connected via a SCART (provided the TV set supports this and is in standby mode).

The IP-based interface between the video control server and the STB also enables the transmission of an acknowledgement that the Tln has read the SMS/MMS.

If the STB is not online, this is indicated to the video control server by the absence of a logon of the STB allocation. In this case, all received SMS/MMS are stored in the SMS/MMS application of the Tln. On the next logon of the STB application these SMS/MMS are provided in sequence to the Tln via the STB.

The transmission of SMS/MMS takes place in principle via the same paths as previously described. Present STBs, for example, enable text input from IR keyboards. Depending on the facilities of the STB, image information can be input for MMS, e.g. the actual TV image to be transmitted, recordings of an image via a camera connected to the STB, image information stored on an internal hard disk or also on a storage medium that can be plugged into the STB (e.g. USB stick, flash memory card). The last option also permits the import of SMS/MMS messages that are received by a mobile radio device provided the mobile radio device has an external storage medium.

The STB application combines input text and image information and sends this to the SMS/MMS client in the video control server, from where it is forwarded in a suitable format for further onward transmission to the distribution center.

Comparison of alternative solutions with the solution in accordance with the invention

- SMS/MMS can be sent via PSTN to a special PSTN terminal. However, this requires a special terminal that can display SMS and supports the connection and control of a TV set. Furthermore, this typically requires a subscription to the CLIP service, which incurs additional costs particularly for analog PSTN Tln. For MMS, the image information must be fetched from the terminal by means of a modem connection and can then be displayed on a connected TV set. However, the transmission of MMS through terminals of this kind is at present not possible.
- The SMS/MMS distribution center could transmit SMS/MMS messages directly via an IP-based connection to a suitable terminal. If this terminal supports an interface to a TV set, the SMS/MMS content could also

be output via a TV set. This approach requires both a suitable terminal and an IP connection between this terminal and the SMS/MMS distribution center (for disadvantages see the following).

5

4. What advantages result from the technical features in accordance with the invention given under item 3?

- 10 ▪ SMS/MMS can be easily received and transmitted at home on the TV set. This thus provides new applications or user groups for SMS/MMS even without a mobile radio device.
- 15 ▪ The method in accordance with the invention enables a genuine personalization of the recipient delivered SMS/MMS based on the Tln profiles of the video control server. This is an absolute requirement for the delivery of SMS/MMS. Typically, a Tln profile of this kind can distinguish exactly which Tln is using the service at that particular moment. This enables the actual user to be identified and authenticated (by means of a PIN). This
20 is a main advantage compared with a solution whereby an SMS/MMS is sent to a Tln terminal (STB or similar) on the basis of only an IP connection. If the subscription to the IP connection, for example, is a general one for a family, then it is not sufficient to deliver SMS/MMS on
25 the basis of the IP connection, because, for example, a son could view SMS/MMS meant for the father.
- 30 ▪ The transmission of SMS/MMS in accordance with the invention also takes place via the video control server, that undertakes the authorizations for this service, the billing and the onward transmission by means of the SMS/MMS distribution center. It is therefore possible to bill the transmission of SMS/MMS in the original network (in this case a TV network) as is usual at present, with the SMS/MMS distribution center in this case acting only

purely as a gateway. Alternative solutions where the SMS/MMS are transmitted from special terminals directly via the SSM/MMS distribution center would require the present SMS/MMS distribution centers to be expanded by adding Tln management and billing functions.

- Receiving and reading SMS/MMS parallel with TV operation is possible by means of blending technology. Thus, for example, SMS/MMS-based communication while a film is running is possible.
 - SMS can easily be written from the IR keyboard of the STB.
 - MMS with image information such as TV pictures, pictures from external storage media or from external cameras can be transmitted.
 - The IP connection to the STB is used to send MMS. This is a simpler and also cost-optimized solution compared with the approach previously discussed where MMS image information is fetched by an additional modem connection.
 - If SMS and MMS are exclusively exchanged between the Tln and the IP-based video network, it is also possible by means of the method in accordance with the invention to transmit longer SMS (more text characters) or MMS with image information with larger data sizes because it is not necessary to comply with the restrictions of the present mobile radio or PSTN networks. In these cases, the video control server would also act as a distribution center for the SMS/MMS to the video Tln.
 - The method in accordance with the invention uses the normal present interfaces for transmission in the direction of the SMS/MMS distribution center.
- Communication between the video control server and STB can be realized as a manufacturer-proprietary system based on standard IP stacks (TCP/UDP on IP). This enables the method to be realized immediately.

Individual aspects of the method or of the video control
server in accordance with the invention

- 5 ▪ The video control server acts as a gateway for SMS/MMS
to/from its video Tln. To do this, it logs on to the
SMS/MMS distribution center in the name of all its video
Tln.
- 10 ▪ A video Tln is addressed internally in the video network
by the video control server and is thus flexible. In
conjunction with present SMS/MMS distribution centers,
this is an E.164 address. If future SMS/MMS distribution
centers support, for example, a uniform resource
identifier (URI) as a Tln address, this would also be
covered by the method in accordance with the invention.
- 15 ▪ The method guarantees a personalized delivery of SMS/MMS
based on the Tln profile of the video Tln.
- The video control server knows the status of the STB of
the video Tln and handles incoming SMS/MMS accordingly.
- 20 ▪ The method enables a direct exchange of SMS/MMS between
the video Tln via the video control server. The video
control server in this case acts as video network
internal SMS/MMS distribution center.

5. Representation of the procedure of example using an
embodiment of the invention, including drawings

Figure 2 supports the following examples of a description of
the process in accordance with the present invention.

30 Registration

- 1a: The video control server is logged on to the SMS/MMS
distribution center for all its video Tln (based for

example on the E.164 PSTN call number of the video Tln).

- 1b: The STB application of the video Tln logs on to the SMS/MMS client on the video control server.

5

Sequence

An SMS/MMS is transmitted to a video Tln from the mobile radio network.

10

2. The SMS/MMS is transmitted to the PSTN call number of the video Tln and arrives at the distribution center.
3. The distribution center knows on the basis of the logon of the video control server that the video Tln can be reached via the video control server. It forwards the SMS to the video control server using a suitable protocol. On the basis of the call number, the video control server allocates the received SMS/MMS to the correct SMS/MMS client of the video Tln. Successful reception of the SMS is acknowledged by a signal back to the distribution center.
4. Because of the logon of the STB application, the SMS/MMS client knows that the STB of the video Tln is online. The Tln profile can be used to check that the actual addressed recipient has logged on. If this is so, the data content is sent to the application on the STB.
5. The data content is shown on the connected TV set.

30

Option SMS/MMS are exchanged between the video Tln within the video network.

6. The video Tln can directly exchange SM/MMS through the video control server. In this case, the video

35

control server acts as an SMS/MMS distribution
center of the video network.